



## THE CLAIMS:

Please AMEND claims 20 and 22 in accordance with the following:

1. (ORIGINAL) An optical transmission system which transports information over fiber-optic transmission lines of upstream and downstream links, comprising:

(a) an end station comprising:

monitoring signal transmission means for transmitting over the upstream link a monitoring request signal including a monitoring command signal with a first optical wavelength and a response carrier wave with a second optical wavelength which is different from the first optical wavelength, the monitoring command signal requesting a specified repeater to provide information about operating status thereof, the response carrier wave being a carrier wave for the specified repeater to return the requested information as a monitoring response signal, and

operating status receiving means for receiving the monitoring response signal and identifying the operating status of the specified repeater from the received monitoring response signal; and

(b) a repeater comprising:

an upstream optical coupler, attached to the upstream link, which has a first port for splitting off a part of upstream transmission signals including the monitoring request signal sent from said end station and a second port for taking out an optical signal that enters the first port,

an upstream wavelength selection means, coupled to the first port of said upstream optical coupler, for selectively passing the first optical wavelength and reflecting back the second optical wavelength, thereby extracting the monitoring command signal from the monitoring request signal received through said upstream optical coupler while reflecting the response carrier wave back to the first port,

monitoring control means, responsive to the monitoring command signal supplied from said upstream wavelength selection means, for collecting information about operating status of said repeater, and encoding the collected information into a response message signal,

excitation means for supplying a pump beam into the fiber-optic transmission line of the upstream link to perform optical amplification using the fiber-optic transmission line as an amplifying medium,

modulation control means, coupled to said excitation means, for modulating the pump beam with the response message signal, whereby the response message signal is superimposed on the response carrier wave propagating on the upstream link and the resulting monitoring response signal reaches said upstream optical coupler, and

a downstream optical coupler, attached to the downstream link, which has a port to

accept the monitoring response signal from the second port of said upstream optical coupler and direct the monitoring response signal into the downstream link for delivery to said operating status receiving means in said end station.

2. (ORIGINAL) The optical transmission system according to claim 1, wherein said upstream wavelength selection means is a fiber grating device which selectively reflects back the second optical wavelength.

3. (ORIGINAL) The optical transmission system according to claim 1, wherein said modulation control means performs amplitude modulation, thereby causing the response carrier wave to be amplitude-modulated.

4. (ORIGINAL) The optical transmission system according to claim 1, wherein said excitation means comprises a WDM coupler which supplies the modulated pump beam into the fiber-optic transmission line to perform either of forward pumping, backward pumping, and two-way pumping.

5. (ORIGINAL) The optical transmission system according to claim 4, wherein said repeater further comprises an optical isolator disposed between said upstream optical coupler and WDM coupler.

6. (ORIGINAL) The optical transmission system according to claim 1, wherein said excitation means further performs erbium-doped fiber amplification.

7. (ORIGINAL) The optical transmission system according to claim 1, wherein:  
said monitoring signal transmission means stops sending the response carrier wave when incoming optical transmission signals are available on the downstream link; and  
said excitation means further supplies the modulated pump beam into the fiber-optic transmission line of the downstream link, whereby the response message signal is superimposed on the incoming optical transmission signals on the downstream link.

8. (ORIGINAL) The optical transmission system according to claim 1, wherein said modulation control means is configured with a variable modulation factor, including a maximum modulation factor to be applied when in out-of-service state.

9. (ORIGINAL) The optical transmission system according to claim 1, which

comprises a plurality of said repeaters, wherein:

said each repeater further comprises a downstream wavelength selection means coupled to said downstream optical coupler; and

said upstream and downstream wavelength selection means in said plurality of repeaters have the same reflecting wavelength.

10. (ORIGINAL) The optical transmission system according to claim 1, which comprises a plurality of said repeaters, wherein:

said each repeater further comprises a downstream wavelength selection means coupled to said downstream optical coupler; and

said upstream and downstream wavelength selection means in said plurality of repeaters have different reflecting wavelengths from each other.

11. (ORIGINAL) The optical transmission system according to claim 1, which comprises a plurality of said repeaters, wherein:

said repeater further comprises a downstream wavelength selection means coupled to said downstream optical coupler; and

said downstream wavelength selection means in said plurality of repeaters have a common reflecting wavelength that is different from what said upstream wavelength selection means reflect equally.

12. (ORIGINAL) The optical transmission system according to claim 1, wherein:  
the information signals are wavelength-division multiplexed signals having wavelengths of  $\lambda_1$  to  $\lambda_n$  ( $n$ : integer); and

the monitoring signal transmission means assigns either of the shortest wavelength  $\lambda_1$ , the longest wavelength  $\lambda_n$ , and an intermediary wavelength between two consecutive wavelengths  $\lambda_m$  and  $\lambda_{m+1}$  ( $m < n$ ) to the second optical wavelength.

13. (ORIGINAL) An optical transmission system which transports information over fiber-optic transmission lines of upstream and downstream links, comprising:

(a) an end station comprising:  
monitoring signal transmission means for transmitting over the upstream link a monitoring request signal including a monitoring command signal with a first optical wavelength and a response carrier wave with a second optical wavelength which is different from the first optical wavelength, the monitoring command signal requesting a specified repeater to provide information about operating status thereof, the response carrier wave being a carrier wave for

the specified repeater to return the requested information as a monitoring response signal, and  
operating status receiving means for receiving the monitoring response signal and  
identifying the operating status of the specified repeater from the received monitoring response  
signal; and

(b) a repeater comprising:

an upstream optical coupler, attached to the upstream link, which has a first port for  
splitting off a part of upstream transmission signals including the monitoring request signal sent  
from said end station and a second port for taking out an optical signal that enters the first port,

an upstream wavelength selection means, coupled to the first port of said upstream  
optical coupler, for selectively passing the first optical wavelength and reflecting back the second  
optical wavelength, thereby extracting the monitoring command signal from the monitoring  
request signal received through said upstream optical coupler while reflecting the response  
carrier wave back to the first port,

monitoring control means, responsive to the monitoring command signal supplied from  
said upstream wavelength selection means, for collecting information about operating status of  
said repeater, and encoding the collected information into a response message signal,

monitoring response signal generating means, coupled to said monitoring control means,  
for producing a monitoring response signal by using an optical modulator to modulate the  
response carrier wave with the response message signal, the optical modulator using either of  
variable optical attenuation and tuned filtering techniques, and

a downstream optical coupler, attached to the downstream link, which has a port to  
accept the monitoring response signal from the second port of said upstream optical coupler and  
direct the monitoring response signal into the downstream link for delivery to said operating  
status receiving means in said end station.

14. (ORIGINAL) The optical transmission system according to claim 13, wherein said  
optical modulator is disposed between the second port of said upstream optical coupler and said  
downstream optical coupler.

15. (ORIGINAL) An end station in an optical transmission system which transports  
signals over fiber-optic transmission lines of upstream and downstream links, comprising:

monitoring signal transmission means for transmitting over the upstream link a  
monitoring request signal including a monitoring command signal with a first optical wavelength  
and a response carrier wave with a second optical wavelength which is different from the first  
optical wavelength, the monitoring command signal requesting a specified repeater to provide  
information about operating status thereof, the response carrier wave being a carrier wave for

the specified repeater to return the requested information as a monitoring response signal; and  
operating status receiving means for receiving the monitoring response signal and  
identifying the operating status of the specified repeater from the received monitoring response  
signal.

16. (ORIGINAL) A repeater in an optical transmission system which transports  
information over fiber-optic transmission lines of upstream and downstream links, comprising:  
an upstream optical coupler, attached to the upstream link, which has a first port for  
splitting off a part of upstream transmission signals and a second port for taking out an optical  
signal that enters the first port, the split part of the upstream transmission signals including a  
monitoring request signal including a monitoring command signal with a first optical wavelength  
and a response carrier wave with a second optical wavelength which is different from the first  
optical wavelength, the monitoring command signal requesting a specified repeater to provide  
information about operating status thereof, the response carrier wave being a carrier wave for  
the specified repeater to return the requested information as a monitoring response signal;  
an upstream wavelength selection means, coupled to the first port of said upstream  
optical coupler, for selectively passing the first optical wavelength and reflecting back the second  
optical wavelength, thereby extracting the monitoring command signal from the monitoring  
request signal received through said upstream optical coupler while reflecting the response  
carrier wave back to the first port;  
monitoring control means, responsive to the monitoring command signal supplied from  
said upstream wavelength selection means, for collecting information about operating status of  
said repeater, and encoding the collected information into a response message signal;  
excitation means for supplying a pump beam into the fiber-optic transmission line of the  
upstream link to perform optical amplification using the fiber-optic transmission line as an  
amplifying medium;  
modulation control means, coupled to said excitation means, for modulating the pump  
beam with the response message signal, whereby the response message signal is  
superimposed on the response carrier wave propagating on the upstream link and the resulting  
monitoring response signal reaches said upstream optical coupler; and  
a downstream optical coupler, attached to the downstream link, which has a port to  
accept the monitoring response signal from the second port of said upstream optical coupler and  
direct the monitoring response signal into the downstream link.

17. (ORIGINAL) An optical transmission system which transports information over  
fiber-optic transmission lines of upstream and downstream links, comprising:

(a) an end station comprising:

monitoring signal transmission means for transmitting over the upstream link a monitoring request signal including a monitoring command signal with a predetermined optical wavelength and a response carrier wave with the same predetermined optical wavelength, the monitoring command signal requesting a specified repeater to provide information about operating status thereof, the response carrier wave being a carrier wave for the specified repeater to return the requested information as a monitoring response signal, and

operating status receiving means for receiving the monitoring response signal and identifying the operating status of the specified repeater from the received monitoring response signal; and

(b) a repeater comprising:

a first upstream optical coupler, attached to the upstream link, which has a first port for splitting off a part of upstream transmission signals, including the monitoring request signal, and a second port for taking out an optical signal that enters the first port,

an upstream wavelength reflection means, coupled to the first port of said first upstream optical coupler, for selectively reflecting back the predetermined optical wavelength,

a second upstream optical coupler, attached to the upstream link, for receiving the monitoring command signal,

monitoring control means, responsive to the monitoring command signal received by said second upstream optical coupler, for collecting information about operating status of said repeater, and encoding the collected information into a response message signal,

excitation means for supplying a pump beam into the fiber-optic transmission line of the upstream link to perform optical amplification using the fiber-optic transmission line as an amplifying medium,

modulation control means, coupled to said excitation means, for modulating the pump beam with the response message signal, whereby the response message signal is superimposed on the response carrier wave propagating on the upstream link and the resulting monitoring response signal reaches said first upstream optical coupler, and

a downstream optical coupler, attached to the downstream link, which has a port to accept the monitoring response signal from the second port of said first upstream optical coupler and direct the monitoring response signal into the downstream link for delivery to said operating status receiving means in said end station.

18. (ORIGINAL) An end station in an optical transmission system which transports signals over fiber-optic transmission lines of upstream and downstream links, comprising:

monitoring signal transmission means for transmitting over the upstream link a

monitoring request signal including a monitoring command signal with a predetermined optical wavelength and a response carrier wave with the same predetermined optical wavelength, the monitoring command signal requesting a specified repeater to provide information about operating status thereof, the response carrier wave being a carrier wave for the specified repeater to return the requested information as a monitoring response signal; and

operating status receiving means for receiving the monitoring response signal and identifying the operating status of the specified repeater from the received monitoring response signal.

19. (ORIGINAL) A repeater in an optical transmission system which transports information over fiber-optic transmission lines of upstream and downstream links, comprising:

a first upstream optical coupler, attached to the upstream link, which has a first port for splitting off a part of upstream transmission signals and a second port for taking out an optical signal that enters the first port, the split part of the upstream transmission signals including a monitoring request signal including a monitoring command signal with a predetermined optical wavelength and a response carrier wave with the same predetermined optical wavelength, the monitoring command signal requesting said repeater to provide information about operating status thereof, the response carrier wave being a carrier wave for the specified repeater to return the requested information as a monitoring response signal;

an upstream wavelength reflection means, coupled to the first port of said first upstream optical coupler, for selectively reflecting back the predetermined optical wavelength;

a second upstream optical coupler, attached to the upstream link, for receiving the monitoring command signal;

monitoring control means, responsive to the monitoring command signal received by said second upstream optical coupler, for collecting information about operating status of said repeater, and encoding the collected information into a response message signal;

excitation means for supplying a pump beam into the fiber-optic transmission line of the upstream link to perform optical amplification using the fiber-optic transmission line as an amplifying medium;

modulation control means, coupled to said excitation means, for modulating the pump beam with the response message signal, whereby the response message signal is superimposed on the response carrier wave propagating on the upstream link and the resulting monitoring response signal reaches said first upstream optical coupler; and

a downstream optical coupler, attached to the downstream link, which has a port to accept the monitoring response signal from the second port of said first upstream optical coupler and direct the monitoring response signal into the downstream link.

20. (CURRENTLY AMENDED) An optical repeater comprising:  
a monitoring controller producing a monitoring response signal indicating status information of the repeater in accordance with a monitoring request signal propagating through an upstream optical transmission line from ~~an upstream~~ a downstream station and obtained by the repeater from the upstream optical transmission line; and  
a modulation controller modulating an excitation light provided by the repeater to the upstream optical transmission line with the monitoring response signal to thereby superimpose the monitoring response signal on a carrier wave propagating through the upstream optical transmission line.

21. (PREVIOUSLY PRESENTED) An optical repeater as in claim 20, further comprising:  
at least one coupler operable to redirect the monitoring response signal superimposed on the carrier wave propagating through the upstream optical transmission line to the upstream station via a downstream optical transmission line.

22. (CURRENTLY AMENDED) An optical repeater comprising:  
means for producing a monitoring response signal indicating status information of the repeater in accordance with a monitoring request signal propagating through an upstream optical transmission line from ~~an upstream~~ a downstream station and obtained by the repeater from the upstream optical transmission line; and  
means for modulating an excitation light provided by the repeater to the upstream optical transmission line with the monitoring response signal to thereby superimpose the monitoring response signal on a carrier wave propagating through the upstream optical transmission line.

23. (PREVIOUSLY PRESENTED) An optical repeater as in claim 22, further comprising:  
means for redirecting the monitoring response signal superimposed on the carrier wave propagating through the upstream optical transmission line to the upstream station via a downstream optical transmission line.